SCALE: 1 inch = 50 feet

LEGAL DESCRIPTION:

FOUND IRON

ROD & CAP

"LB5091" (1.0' NORTH)

*177.39*°

SET 5/8" IRON

ROD & CAP — "LB4709"

S89°51'39°E

A PORTION OF SECTION 1, TOWNSHIP 18 SOUTH, RANGE 23 EAST, SUMTER COUNTY, FLORIDA, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS:

BEGIN AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SAID SECTION 1; THENCE S89°51'39"E, ALONG THE NORTH LINE OF SAID NORTHEAST 1/4 A DISTANCE OF 451.19 FEET; THENCE DEPARTING SAID NORTH LINE SOO'08'22"W, 42.65 FEET TO A POINT OF CURVATURE OF A 53.00 FOOT RADIUS NON-TANGENT CURVE CONCAVE TO THE SOUTHWEST AND HAVING A CHORD BEARING AND DISTANCE OF \$31"55'35"E, 90.00 FEET WHOSE RADIUS POINT BEARS \$0002'19"E; THENCE SOUTHEASTERLY ALONG SAID CURVE THROUGH A CENTRAL ANGLE OF 11673'27" AN ARC DISTANCE OF 107.51 FEET; THENCE S89°50'07"E, 230.63 FEET; THENCE N00°09'53"E, 119.02 FEET TO A POINT ON SAID NORTH LINE; THENCE S89°51'39"E, ALONG SAID NORTH LINE A DISTANCE OF 177.39 FEET; THENCE DEPARTING SAID NORTH LINE S00°08'21"W, 101.30 FEET TO A POINT 10.00 FEET NORTHWESTERLY OF AS MEASURED AT RIGHT ANGLES TO THE NORTHWESTERLY BOUNDARY LINE OF LOT 8, COUNTY CROSSINGS SUBDIVISION, AS PER PLAT THEREOF RECORDED IN PLAT BOOK 6, PAGES 3 AND 3A, PUBLIC RECORDS OF SUMTER COUNTY, FLORIDA; THENCE S4812'36"W, ALONG A LINE PARALLEL WITH AND 10.00 FEET NORTHWESTERLY OF AS MEASURED AT RIGHT ANGLES TO SAID NORTHWESTERLY BOUNDARY LINE OF LOT 8 A DISTANCE OF 367.56 FEET; THENCE S41'47'24"E, 10.00 FEET TO SAID NORTHWESTERLY BOUNDARY LINE; THENCE S48'12'36"W, ALONG SAID NORTHWESTERLY BOUNDARY LINE A DISTANCE OF 402.08 FEET, THENCE DEPARTING SAID NORTHWESTERLY BOUNDARY LINE N41°45'54"W, 50.00 FEET TO A POINT 50.00 FEET NORTHWESTERLY OF AS MEASURED AT RIGHT ANGLES TO SAID NORTHWESTERLY BOUNDARY LINE; THENCE S48"12'36"W, ALONG A LINE PARALLEL WITH AND 50.00 FEET NORTHWESTERLY OF AS MEASURED AT RIGHT ANGLES TO SAID NORTHWESTERLY BOUNDARY LINE OF LOT 8 A DISTANCE OF 125.87 FEET; THENCE DEPARTING SAID LINE N41°44'13"W, 292.39 FEET TO A POINT OF CURVATURE OF A 270.00 FOOT RADIUS CURVE CONCAVE TO THE NORTHEAST; THENCE NORTHWESTERLY ALONG SAID CURVE THROUGH A CENTRAL ANGLE OF 12"18'41" AN ARC DISTANCE OF 58.02 FEET TO A POINT ON THE EASTERLY EXTENSION OF THE SOUTHEASTERLY BOUNDARY LINE OF LOT 10, BLOCK 36, OF COMMERCIAL HIGHLANDS, AS PER PLAT THEREOF RECORDED IN PLAT BOOK 3, PAGE 47, PUBLIC RECORDS OF SUMTER COUNTY, FLORIDA; THENCE S48'08'17"W, ALONG SAID LINE 80.41 FEET TO THE NORTHEASTERLY CORNER OF SAID LOT 10, BLOCK 36; THENCE N41°45'27"W, ALONG THE NORTHEASTERLY BOUNDARY LINE OF LOTS 6 THROUGH 10. BLOCK 36. OF SAID COMMERCIAL HIGHLANDS A DISTANCE OF 249.98 FEET TO THE NORTHWESTERLY CORNER OF SAID LOT 6, BLOCK 36; THENCE N48°10'17"E, ALONG THE EASTERLY EXTENSION OF SAID LOT 6, BLOCK 36 A DISTANCE OF 180.36 FEET; THENCE N41°45'46"W, 204.84 FEET TO A POINT ON THE NORTH LINE OF THE NORTHWEST 1/4 OF SAID SECTION 1; THENCE S89°50'31"E, ALONG SAID NORTH LINE A DISTANCE OF 244.33 FEET TO THE POINT OF BEGINNING. CONTAINING 10.27 ACRES, MORE OR LESS.

### ABBREVIATIONS: SYMBOLS LEGEND:

DENOTES IRRIGATION CONTROL VALVE = OFFICIAL RECORDS BOOK DENOTES SANITARY MANHOLE = LICENSED BUSINESS = CENTERLINE \$>FH DENOTES FIRE HYDRANT R/W = RIGHT-OF-WAYDENOTES CABLE TELEVISION RISER CONC. = CONCRETEDENOTES STORM MANHOLE = RADIUS = ARC LENGTH DENOTES LIGHT POLE

= CENTRAL ANGLE DENOTES TELEPHONE RISER = CHORD DISTANCE DENOTES WATER VALVE = CHORD BEARING = IDENTIFICATION DENOTES CATCH BASIN = FIRE HYDRANT = ELEVATION

DENOTES ELECTRICAL BOX = REINFORCED CONCRETE PIPE = POLYVINYL CHLORIDE PIPE DENOTES SET 5/8" IRON ROD & CAP "LB 4709" = SANITARY MANHOLE DENOTES SET NAIL & DISC "LB 4709" = LIGHT POLE DENOTES NUMBER OF PARKING SPACES = GAS VALVE DENOTES NUMBER OF PARKING SPACES

**B**BFP DENOTES BACK FLOW PREVENTOR

# SURVEYOR'S NOTES:

= CATCH BASIN

EXISTING AT THAT TIME.

- . UNLESS IT BEARS THE SIGNATURE AND ORIGINAL RAISED SEAL OF A FLORIDA LICENSED SURVEYOR AND MAPPER, THIS BOUNDARY SURVEY IS FOR INFORMATIONAL PURPOSES ONLY AND IS NOT VALID.
- 2. CERTIFICATION IS LIMITED TO PARTIES NAMED HEREON.
- 3. BEARINGS SHOWN HEREON ARE ASSUMED AND REFERRED TO THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 1-18-23, HAVING A BEARING OF S89°51'39"E.
- 4. VISIBLE EASEMENTS OR ENCROACHMENTS ARE SHOWN OR NOTED HEREON. 5. UNDERGROUND: IMPROVEMENTS AND UTILITIES NOT LOCATED.
- 6. THE SYMBOLS REFLECTED IN THE LEGEND AND ON THIS SURVEY MAY HAVE BEEN ENLARGED FOR CLARITY. THE SYMBOLS HAVE BEEN PLOTTED AT THE CENTER OF THE FIELD LOCATION AND MAY NOT REPRESENT THE ACTUAL SHAPE OR SIZE OF THE FEATURE.
- 7. THE INFORMATION DEPICTED ON THIS MAP REPRESENTS THE RESULTS OF THE SURVEY ON THE DATE INDICATED AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS
- 8. THE ACCURACY FOR THE SURVEY MEASUREMENTS SHOWN HEREON MEETS OR EXCEEDS THE EXPECTED USE OF THE LANDS SHOWN. (COMMERCIAL/HIGH RISK) 1 FOOT IN 10,000 FEET.
- 9. ELEVATIONS SHOWN HEREON ARE BASED ON THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88), AND IS BASED ON NGS POINT "SUMTER 41"

## NATIONAL FLOOD INSURANCE PROGRAM:

SAID DESCRIBED PROPERTY APPEARS TO BE LOCATED IN FLOOD ZONE 'C' (AREAS OUTSIDE THE 500-YEAR FLOOD PLAIN) PER F.I.R.M. NUMBER 120296 0075 B; DATED 3-15-82. THIS SURVEYOR MAKES NO GUARANTEES AS TO THE ACCURACY OF THE ABOVE INFORMATION. THE LOCAL F.E.M.A. AGENT SHOULD BE CONTACTED FOR VERIFICATION.

**SURVEYOR'S CERTIFICATE:** 

I HEREBY CERTIFY THAT THE ABOVE MENTIONED MAP OF LAND SURVEY, AND THE FIELD SURVEY ON WHICH IT IS BASED, IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AS PREPARED UNDER MY DIRECTION AND SUPERVISION. I FURTHER CERTIFY THAT THIS SURVEY MEETS THE APPLICABLE REQUIREMENTS OF THE MINIMUM TECHNICAL STANDARDS FOR LAND SURVEYS IN THE STATE OF FLORIDA (CHAPTER 61G17-6 FLORIDA ADMINISTRATIVE CODE) PURSUANT TO SECTION 472.027, FLORIDA STATUTES.

JULY 10, 2009

ALEXANDER DUCHART, PROFESSIONAL SURVEYOR & MAPPER FLORIDA REGISTRATION NO. 5998

ENGINEERS SURVEYORS PLANNERS LB 4709 444

CLIENT CHARACTER-OAKS JOB NO. 6<u>5146-0004</u> DRAWN BY \_\_\_\_\_GW CHKD BY FIELD DATE <u>5-25-09</u> FLD. BK/PG<u>V09-05-1</u>

SHT. SI OF SI

SET 5/8" IRON 20"oak CONC. MONUMENT ROD & CAP\_ \_\_NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 1-18-23 (No I.D.) "LB4709" 244.33' S89°50'31"E <u> S89°51'39°E 451.19'</u> 36"oak 48"oak 36"oak 50"oak S00'08'22"W L=107.51' R=53.00' **4-11673'27"** CH.=90.00° CB.=S31°55'35°E S89'50'07"E 230.63" SET 5/8" IRON ROD & CAP — "LB4709" AREA= 10.27 ACRES± NE 86TH. TERRACE . (ACCESS EASEMENT '2' PER ORB 1942, PAGE 232) FOUND IRON "No 1.D." NE 86th DRIVE (ACCESS EASEMENT PER ORB 1942, PAGE 232) SET 5/8" IRON ROD & CAP ---SET 5/8" IRON NE 138TH. LANE . ROD & CAP (ACCESS EASEMENT '2' PER ORB 1942, PAGE 232) FOUND IRON COMMERCIA PAGE "COUNTY CROSSINGS SUBDIVISION" SET 5/8" IRON PLAT BOOK "6", PAGES 3 & 3A - ROD & CAP EXISTING SIGN EASEMEN "LB4709" *50.00*° S N41'45'46"W 125.87 S4872'36"W TOTAL TOTAL A PO

TRACT 'E'

THE N.W. CURNER OF THE N.E. 177 O.
SECTION 1, TOWNSHIP 18 SOUTH, RANGE 23 EAST PLAT BOOK 7, PAGES 5 TO 8 BOTH INCLUSIVE

"SOUTHERN RIDGE AT STONECREST"

- 88' POWER EASEMENT PER ORB 1916, PAGE 118

& ORB 1774, PAGE 1344

POINT OF BEGINNING

THE N.W. CORNER OF THE N.E. 1/4 OF

LOT 4

"STONECREST SOUTH COMMERCIAL"

PLAT BOOK 8, PAGES 30 TO 34 BOTH INCLUSIVE

NORTH LINE OF THE NORTHWEST 1/4 OF SECTION 1-18-23-

SCALE \_\_\_\_*1"=50'* 

SEAL